



Automatic
PAD CLEAN!



on ink cup model only

FEATURES

- Single or 2 color user-friendly pad printer
- Rigid aluminium casting machine frame
- Use sealed ink cup or open ink tray set up
- Compatible with long life, economy of **Green plate**, 10 mm steel plate, thin steel plate and polymer plate
- Dead-on printing plate registration for quick job change
- Membrane switch control panel
- Automatic pad clean with programmable cleaning cycle (on ink cup model only)
- Special functions: double ink / print cycles, dwell and delay before print
- Digital pad stroke (DPS) for variable printing depth
- Hardened ground steel shaft with impregnated bushing ensure friction-free movement
- High speed and smooth machine operations

SPECIFICATIONS


| | |
|------------------------------|-----------------------------|
| Ink cup : | Ø60, 70, 90 mm |
| Ink cup plate size : | 100 x 250 mm |
| Ink tray plate size : | 100 x 100, 150, 200, 300 mm |
| Max. speed : (dry cycle) * | 1,800 cycles/hr. |
| Max. pad pressure : | 750N at 6 bar |
| Power : | 110/220V 50/60Hz 20W |
| Air consumption : | 96 litre/min. (approx.) |
| Size (LxWxH) : Ink cup model | 690 x 600 x 570 mm |
| Ink tray model | 660 x 300 x 570 mm |
| Weight : Ink cup model | 46 kg (approx.) |
| Ink tray model | 45 kg (approx.) |

* Please note that actual output may be affected by print requirement, ink drying condition, load/unload arrangement, pad stroke speed, pad hardness, production setup, product quality and production control.

OPTIONAL




- Open ink tray model
- Newly improved MS-100 machine stand enhances stability



- 2 individual X,Y angle platform/work table with independent adjustment



- 2 color pneumatic conveyor



- 2 color pneumatic shuttle